



Electro Standards Laboratories
ADVANCED SYSTEMS DESIGN & SERVICES

SPECIFICATIONS MODEL 4505 (Cat. No. 304505)

Model 4505 DB9 A/B/C/D Switch with Manual Operation

- Ideal for device-sharing applications; Applicable to ANY DB9 interface devices

INTRODUCTION

The Model 4505 DB9 A/B/C/D Switch allows the user to reroute data between any one of four devices to one COMMON device with the simple rotation of a selector switch. All nine pins of the DB9 interface are supported. No need to plug and unplug interconnection cables thereby eliminating connector wear and/or errors when reconfiguring networks. The Model 4505 is packaged in a slim desktop style enclosure.

FEATURES

- Allows quick connection to any one of four devices from one COMMON device.
- High quality sealed switch with self wiping contacts.
- The switch ports are transparent to all data.
- **All (9) pins of the DB9 interface are switched via break-before-make rotary switch.**
- Eliminates the need to plug and unplug cables.
- Manual operation, no power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- **Lifetime warranty against manufacturing defects.**
- Custom length DB9 cables available for your switch installation.



SPECIFICATIONS:

PORT CONNECTORS: (5) DB9 female connectors labeled A, B, C, D, and COMMON.

FRONT PANEL CONTROL: (1) Front panel rotary switch allows selection of switch position.

POWER: No power required.

DIMENSIONS: 4.18" W x 1.75" H x 6.68" D.
 (10.7 x 4.5 x 17 cm)

WEIGHT: Approximately 1.2 lbs. (0.6 kg)

Custom Length DB9 cables available for your switch installation. State cable length (XXX) when ordering.

Part Number	Description
990127-XXX	XXX Feet, DB9 F/F, 9-Conductor Unshielded PVC Cable
990125-XXX	XXX Feet, DB9 M/F, 9-Conductor Unshielded PVC Cable
990126-XXX	XXX Feet, DB9 M/M, 9-Conductor Unshielded PVC Cable

MODEL 4505 APPLICATION: SWITCHES DB9 INTERFACE

