

## Model 5150 Keylock Video Conference Room Secure Switching System

### “NON-SECURE” Mode (Key in DATA PASS position)

In this mode, the Electro Standards Laboratories' Model 5150 Video Conference Room Secure Switching System **passes** the connection of copper and fiber voice and data lines from the conference room equipment to the building data network.

### “SECURE” Mode (Key in OFF-LINE position)

In this mode, the Model 5150 Video Conference Room Secure Switching System **disconnects** the same set of lines from the building data network, isolating all of the conference room equipment, completely.

Install the **Model 5150 Secure Switching System** with listed modules, or customize with the assistance of “The Switch Experts” - Electro Standards Laboratories!

### SECURE/NON-SECURE SYSTEM STATUS INDICATOR

- **Model 5008** Display Indicator connects to status ports of all four system switches via daisy chain cables.

### Keylock DATA PASS/OFF-LINE Switches

- **Model 5200** Fiber Optic Switch.  
Multimode Duplex SC connectors (2 Fiber Strands). **2 Paths.**
- **Model 5502** Ethernet Switch.  
RJ-45 Connectors (Pins 1, 2, 3 and 6). **16 Channels.**
- **Model 5503** Telco Switch.  
RJ-11/12 connectors (Center 4 pins). **16 Channels.**
- **Model 5504** ISDN Switch.  
RJ-45 connectors (Pins 3, 4, 5 and 6). **6 Channels.**

★ **Municipalities, schools, government: This product is on GSA Schedule!**



System Model 5150 shown above

