

## PathWay® Model 7200 Single Channel DB9 A/B Switch, with RS232 Remote, Desktop

### INTRODUCTION:

The PathWay® Model 7200 Single Channel DB9 A/B Switch with RS232 Remote allows the user the capability of sharing a single port interface device connected to the "COMMON" port among two other devices connected to the "A" and "B" ports, with remote access functionality. The Model 7200 is packaged in a slim desktop style enclosure.

The switch may be controlled locally by manually operating the front panel push button or remotely from the DB9 female serial interface Remote port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

### FEATURES:

- Allows quick connection to any one of two DB9 interface devices from one COMMON device.
- Switches all 9 pins of the DB9 interface.
- Transparent to data speed and format.
- Local control via front-panel pushbutton.
- Remote RS232 ASCII commands that allow the user to control switch position, lockout front panel operations and obtain switch status.
- Front panel LED's display switch position and power status.
- Retains last switch position in the event of power loss and continues to pass data.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB9 cables available for your switch installation.

★ **Municipalities, schools, government:**  
**This product on GSA Schedule!**



### SPECIFICATIONS:

**PORT CONNECTORS:** (3) DB9 (F) connectors labeled A, B, and COMMON.

**FRONT PANEL CONTROL:** (1) Manual pushbutton allows local switching.

**DISPLAY:** (2) Front panel LED's display switch position and power status.

**REMOTE CONTROL:** (1) DB9 Female connector on rear panel accepts ASCII RS232 Serial Data for remote control operation.

**POWER:** UL approved 100VAC/240VAC, 50Hz/60Hz wall mount power module supplies 12 VDC, 500mA to the unit. Has 2-prong, US, non-polarized plug.

**DIMENSIONS:** Desktop, 7.75" W x 7.25" D x 2.0" H. (19.7 x 18.4 x 5.1 cm)

**WEIGHT:** Approximately 2.5 lbs. (1 Kg)

### OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC/240VAC, 50Hz/60Hz in place of standard power module. Has IEC 60320 C14 inlet. **Ideal for international applications.**

### APPLICATION: Model 7200

