

PathWay® Model 7201 DB9 A/B/C/D Switch with RS232 Remote Control, Desktop

- **Ideal for device-sharing applications such as Audio/Video and Security Camera Monitoring Systems. Applicable to ANY DB9 interface devices.**

INTRODUCTION

The PathWay® Model 7201 DB9 A/B/C/D Switch with RS232 Remote allows the user the capability of sharing a single DB9 interface device connected to the Common port among four other devices connected to the "A", "B", "C", and "D" ports. The Model 7201 is packaged in a slim desktop style enclosure.

The Model 7201 can be switched locally by using its front panel pushbutton or remotely from the DB9 RS232 Serial Interface Remote port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- **Compatible with most Audio/Video Controller Systems such as AMX A/V Controllers and Creston Programmable Controller.**
- Allows quick connection to any one of four devices from one COMMON device.
- Switches all 9 pins of the DB9 interface.
- Transparent to data speed and format.
- Eliminates the need to plug and unplug cables.
- Local control via front-panel pushbutton.
- Remote RS232 ASCII Commands that allow the user to control switch position and obtain switch status.
- Front panel LED's display present position and power status.
- Retains last set position in the event of power loss and continues to pass data.
- Attractive anodized aluminum black box packaging provides EMI/RFI shielding.
- Desktop configuration is standard.



SPECIFICATIONS:

PORT CONNECTORS: (5) DB9(F) connectors labeled A, B, C, D and COMMON.

REMOTE CONTROL: (1) DB9(F) connector labeled REMOTE accepts RS232 serial data ASCII commands.

FRONT PANEL CONTROL: (1) Manual pushbutton allows local switching.

DISPLAY: (4) LED's labeled A, B, C and D display switch position and (1) LED labeled POWER displays power status.

POWER: UL approved 100VAC/240VAC, 50Hz/60Hz wall mount power module supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug.

DIMENSIONS: Desktop configuration 8.15" W x 3.11" H x 7.27" D. (20.8 x 7.9 x 18.5 cm)

WEIGHT: Approximately 2.1 lbs. (1.0 Kg)

WIDE RANGE POWER OPTION AVAILABLE:

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC/240VAC, 50Hz/60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

MODEL 7201 APPLICATION:

