

PathWay® Model 7207 DB9 A/B/C/D Switch with Exclusive Remote Control

- **Ideal for IT Network Management of Multiple Remote Locations.**
- **Switch ANY DB9 Interface Device to share or backup.**

INTRODUCTION

The PathWay® Model 7207 DB9 A/B/C/D Switch with RS232 Remote allows the user the capability of sharing a single DB9 Interface device connected to the Common port among four other devices connected to the "A", "B", "C", and "D" ports. The Model 7207 is packaged in a slim desktop style enclosure.

There is no "local" or front panel switch controls on the unit. The Model 7207 can ONLY be switched remotely from the DB9/female RS232 Serial Interface Remote port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

FEATURES:

- Allows quick connection to any one of four devices from one COMMON device.
- The switch ports are transparent to all data.
- **All (9) pins of the DB9 interface are switched via break-before-make electromechanical relays.**
- Eliminates the need to plug and unplug cables.
- The unit maintains last set position on power loss and continues to pass data.
- The REMOTE RS232 ASCII commands that allow the user to control switch position, obtain switch status, query firmware version number and query serial number.
- **Ideal for "remote control only" applications. There is no local control on the Model 7207.**
- Front-panel LED's display switch position and power status.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length DB9 cables available for your switch installation.
- ★ **Municipalities, schools, government: This product on GSA Schedule!**



SPECIFICATIONS:

PORT CONNECTORS: (5) DB9(F) connectors labeled A, B, C, D and COMMON.

REMOTE CONTROL: (1) DB9(F) connector labeled REMOTE accepts RS232 serial data ASCII commands for Remote Control operation.

DISPLAY: (4) LED's labeled A, B, C and D display switch position. (1) LED labeled POWER displays power position.

POWER: UL approved wall mount 100VAC/240VAC, 50Hz/60Hz power module supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug.

DIMENSIONS: Desktop configuration 8.10" W x 2.41" H x 7.30" D. (20.6 x 6.2 x 18.6 cm)

WEIGHT: Approximately 2.0 lbs. (0.9 kg)

WIDE RANGE POWER OPTION AVAILABLE:

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC/240VAC, 50Hz/60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

PathWay® Model 7207 A/B/C/D Application:

