

## PathWay® Model 7208-CC DB15 A/B/C/D Switch with Contact Closure Remote

- **Switching exclusively controlled by remote port**

### INTRODUCTION

The PathWay® Model 7208-CC DB15 Interface A/B/C/D Switch provides switching in a compact desktop unit. It allows the user the capability of sharing a single DB15 interface device connected to the Common port among four other devices connected to the "A", "B", "C", and "D" ports.

There is no "local" or front panel switch controls on the unit. The Model 7208-CC can ONLY be switched remotely from the HD15 / female Contact Closure Control port located on the rear of the unit. The front panel LED display indicates the switch position and unit power status.

The switched DB15 / female ports (A, B, C, D, and COMMON) are transparent to all data. All 15 signals of the DB15 connector interface are switched.

### FEATURES:

- Allows quick connection to any one of four devices from one COMMON device.
- **There is no "local" or front panel control.**
- A HD15 / female REMOTE port allows remote control of the unit based on a Contact Closure transition signals.
- REMOTE port allows change of position and query of switch position.
- All DB15 leads switched.
- Transparent to data speed and format.
- Front panel LED indicators display the switch position and power status.
- Switch position and connection through the switch maintained during power loss.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Custom length DB15 cables available for your switch installation.



### SPECIFICATIONS:

**PORT CONNECTORS:** (5) DB15 female connectors labeled A, B, C, D and COMMON.

**DISPLAY:** (5) Front panel LED's display switch position and power status.

**REMOTE CONTROL:** (1) HD15 female connector on rear panel accepts contact closure transition signals for Remote Control operation.

**POWER:** UL approved wall mount 100VAC/240VAC, 50Hz/60Hz power module supplies 12 VDC, 500 mA to the unit. Has 2-prong, US, non-polarized plug.

**DIMENSIONS:** Desktop Configuration, 7.75" W x 2.0" H x 7.25" D. (19.7 x 5.1 x 18.4 cm)

**WEIGHT:** Approximately 3.0 lbs. (1.0 Kg)

### OPTION: WIDE RANGE POWER MODULE

(Cat No 517277) **CE, RoHS, and UL** listed table mount power module, 100VAC/240VAC, 50Hz/60Hz for use in place of standard power module that is included with the unit. Has IEC 60320 C14 inlet. **Ideal for international applications.**

### MODEL 7208-CC APPLICATION:

