

LineSelect™ Model 8093 DB9 A/B Switch, All F Connectors, Manual, Desktop

• Adds efficiency to network; allows sharing of ANY DB9 interface devices.

INTRODUCTION

The **LineSelect™** Model 8093 allows the user to access two DB9 devices connected to the A and B ports from one DB9 device connected to the COMMON port. Switching between devices A and B is quick and easy via the front panel rotary selector - No need to plug and unplug cables; no chance for network reconfiguration errors. The Model 8093 is packaged in a slim desktop style enclosure.

FEATURES

- Allows quick connection to any one of two DB9 interface devices from one COMMON device.
- Manual operation via front-panel rotary switch.
- High quality sealed switch with self-wiping low impedance contacts.
- Transparent to data speed and format.
- **All (9) pins of the DB9 interface are switched via a break-before-make rotary switch.**
- Eliminates the need to plug and unplug cables.
- Improves computer network network efficiency by allowing sharing or peripherals.
- No external power required.
- Attractive anodized black box packaging provides EMI/RFI shielding.
- Also available with MMF connectors. See Model 8092, Cat. No. 304380.
- Custom length DB9 cables available for your switch installation.
- **Lifetime warranty against manufacturing defects.**



SPECIFICATIONS:

- CONNECTORS:** (3) DB9(F) ports on rear panel.
CONTROL: (1) Rotary switch on front panel selects A or B.
PINS SWITCHED: All 9 pins switched.
POWER: No power required.
ENCLOSURE: Shielded Aluminum Enclosure.
DIMENSIONS: 5.25" W x 2.0" H x 7.25" D.
 (13.3 x 5.1 x 18.4 cm)
WEIGHT: Approximately 1.5 lbs (0.7 kg)

Custom Length DB9 cables available for your switch installation. State cable length (XXX) when ordering.

Part Number	Description	Price
990127-XXX	XXX Feet, DB9 F/F, 9-Conductor Unshielded PVC Cable	Call for price
990125-XXX	XXX Feet, DB9 M/F, 9-Conductor Unshielded PVC Cable	Call for price
990126-XXX	XXX Feet, DB9 M/M, 9-Conductor Unshielded PVC Cable	Call for price

LineSelect™ Model 8093 Application Diagram

