

Model 9426 Dual-Channel, DB9 12-to-1 Switch, Manual, Rackmount

- Applicable to switching ANY DB9 network or device including surveillance cameras, POS/Cash Registers, PC Serial data ports, and more!

INTRODUCTION

The Model 9426 Switch system is comprised of two independent sharing switches efficiently packaged in a 19-inch wide 2U high (3.5") rackmount unit. Allows the user to independently switch each of the two channels manually via two knobs located on the front panel. The Model 9426 all metal black chassis is designed to provide EMI/RFI shielding and to fit in standard 19" rack.

FEATURES:

- Each channel allows quick connection to any one of 12 DB9 interface devices or networks from one COMMON device.
- Manual operation via front-panel rotary switches.
- Independently switch each of the 2 channels.
- High quality sealed switches with self-wiping low impedance contacts.
- **All 9 pins of the DB9 interface are switched via break-before-make rotary switches.**
- The switch ports are transparent to all data.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length DB9 cables available for your switch installation.
- Lifetime warranty against manufacturing defects.



SPECIFICATIONS:

PORT CONNECTORS: (13) DB9 female connectors labeled 1 through 12, and COMMON for each channel.

FRONT PANEL CONTROLS: (2) Manual rotary switches allow local switching.

DIMENSIONS: Rackmount 19.0" W x 3.5" H x 8.77" D. (48.3 x 8.9 x 22.3 cm)

WEIGHT: 6.2 lbs. (2.8 kg)

Do you require other switch functions?

Contact ESL for assistance:

www.ElectroStandards.com

... The Worlds Leading Supplier of Data Network Switches!

MODEL 9426 APPLICATION:

