

## Model 9434 DB9 A/B/C/D Switch, Manual, Rackmount

• **Ideal for device-sharing applications; Applicable to ANY DB9 interface devices.**

### INTRODUCTION

The Model 9434 DB9 A/B/C/D Switch allows the user to reroute data between any one of four devices to one COMMON device with the simple rotation of a selector switch. All nine pins of the DB9 interface are supported. No need to plug and unplug interconnection cables thereby eliminating connector wear and/or errors when reconfiguring networks. The Model 9434 is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.



### FEATURES

- Allows quick connection to any one of four devices from one COMMON port.
  - Manual operation via front-panel rotary switch.
  - High quality sealed switch with self-wiping precious metal contacts.
  - Eliminates the need to plug and unplug cables.
  - Transparent to data speed and format.
  - All 9 pins of the DB9 interface are switched via break-before-make rotary switch.
  - No external power required.
  - Attractive all metal black box packaging provides EMI/RFI shielding.
  - Custom length DB9 cables available for your switch installation.
  - Lifetime warranty against manufacturing defects.
- ★ **Municipalities, schools, government: This product on GSA Schedule!**

### SPECIFICATIONS:

**PORT CONNECTORS:** (5) DB9 female connectors on rear panel labeled A, B, C, D, and COMMON.

**FRONT PANEL CONTROL:** (1) Rotary switch on front panel selects A, B, C, or D.

**POWER:** No power required. Manually operated.

**DIMENSIONS:** 19.0" W x 1.75" H x 8" D.  
(48.3 x 4.4 x 20.3 cm)

**WEIGHT:** Approximately 4.3 lbs. (2.0 kg)

**Custom Length DB9 cables available for your switch installation. State cable length (XXX) when ordering.**

Part Number	Description
990127-XXX	XXX Feet, DB9 F/F, 9-Conductor Unshielded PVC Cable
990125-XXX	XXX Feet, DB9 M/F, 9-Conductor Unshielded PVC Cable
990126-XXX	XXX Feet, DB9 M/M, 9-Conductor Unshielded PVC Cable

### MODEL 9434 APPLICATION:

