

Model 9451R DB25 A/B/C Switch, Manual, Rackmount

- Provides reliable network backup for mission critical systems.
- Applicable to switching ANY DB25 interface devices.

INTRODUCTION

The Model 9451R DB25 A/B/C Switch allows the user to access three DB25 devices connected to its A, B, and C ports with one DB25 device connected to its COMMON port. The unit is manually operated, requiring no power. Port selection is quick and easy via a front panel rotary switch. The Model 9451R is enclosed in a 1U, full rack size, all metal black chassis designed to provide EMI/RFI shielding and fit in a standard 19" rack.

FEATURES:

- Allows quick connection to any one of three DB25 devices or networks from one COMMON device or network.
- **RoHS, REACH, and SVCH compliant.**
- Manual operation via front-panel rotary switch.
- High quality sealed switch with self-wiping low impedance contacts.
- Transparent to data speed and format.
- All 25 pins of the DB25 interface are switched via break-before-make rotary switch.
- Eliminates the need to plug and unplug cables.
- No external power required.
- Attractive all metal black box packaging provides EMI/RFI shielding.
- Custom length DB25 cables available for your switch installation.
- **Lifetime warranty against manufacturing defects.**

Model 9451R DB25 A/B/C Switch



SPECIFICATIONS:

PORT CONNECTORS: (4) DB25 female connectors labeled A, B, C and COMMON.

FRONT PANEL CONTROL: (1) Rotary switch on front panel selects A, B, C.

LIFE: 10,000 cycles at the rate of 20-25 cycles/minute and no load.

OPERATING & STORAGE TEMP: -10° C to +60° C.

POWER: No power required. Manually operated.

DIMENSIONS: Rackmount 19.0" W x 1.75" H x 8.75" D. (48.3 x 4.5 x 22.3 cm)

WEIGHT: Approximately 4.4 lbs. (2.0 kg)

Ask about our popular

Model 700 RS232 Breakout Box

Tri-State LED's monitor the data interface and "TELL ALL" for fault isolation.



Custom length data network cables 25-conductor, DB25/DB25, Unshielded, PVC.

Part Number	Connectors	Length Specify XXX-FT	Price (USD)
990104-XXX	F/F	XXX-FT	\$24.00 + 0.55 / FT
990105-XXX	M/F	XXX-FT	\$24.00 + 0.55 / FT
990106-XXX	M/M	XXX-FT	\$24.00 + 0.55 / FT

Model 9451R Application

